

product application chart

VDOT NUMBER	PRODUCT NUMBER	SIZES	Asphalt	Backfill for Underground Cables	Barns	Bicycle Trails	Bridging Muddy Areas	Concrete Slab Bedding	Concrete (Ready-Mix)	Crawl Spaces	Culvert and Large Pipe Bedding	Driveways	Erosion Control	Filter Stone	Finishing Driveways	French Drains	Highway Underdrain Construction	Ice and Snow Traction	Kennel Runs	Landscaping	Parking Areas	Pathways	Railroad Ballast	Residential Drains	Riding Rings	Road Base	Road Sub-base	Roofing Stone	Septic Drain Fields	Silt Traps	Splash Guards	Stables	Stabilizing Soft Terrain	Stacked Walls	Stream Bank Stabilization	Walkways	
1	1	3 1/2" - 3/4" (90 mm - 19.0 mm)					•					•	•							•										•					•		
2	2	2 1/2" - 1/2" (63 mm - 12.5 mm)					•					•	•							•										•							
3	3	2" - 1/2" (50 mm - 12.5 mm)					•					•	•							•										•							
Rail Ballast	4	2" - 3/8" (50 mm - 9.5 mm)					•					•	•							•			•						•								
5	5	1" - 3/8" (25 mm - 9.5 mm)	•					•			•			•		•				•				•					•								
357	6	1 1/2" - 3/16" (37.5 mm - 4.75 mm)												•		•				•				•					•								
56	56	1" - 3/16" (25 mm - 4.75 mm)	•					•								•				•				•					•								
57	57	1" - 3/32" (25 mm - 2.36 mm)	•					•	•			•								•	•										•						
68	68	3/4" - 3/8" (19 mm - 1.18 mm)	•			•			•			•				•				•	•	•									•					•	
78	78	1/2" - 3/8" (12.5 mm - 1.18 mm)	•			•						•				•				•	•	•					•				•					•	
8	8	3/8" - 3/8" (9.5 mm - 1.18 mm)	•						•							•			•	•				•					•								
8P	8P	3/8" - 3/32" (9.5 mm - 2.36 mm)	•						•							•			•	•				•					•								
9	9	3/16" - 1/8" (4.75 mm - 300 µm)	•													•	•	•																			
10	10	3/16" MAX (4.75 mm)	•	•	•	•		•	•	•	•							•	•	•			•									•	•			•	
B slurry	13	3/16" MAX (4.75 mm)	•	•	•	•		•	•	•	•							•	•	•			•									•	•			•	
C slurry	14	3/16" MAX (4.75 mm)	•	•	•	•		•	•	•	•							•	•	•			•										•	•			•
B-sand	16	3/16" MAX (4.75 mm)	•	•	•	•			•	•								•	•	•			•									•					•
Washed #10	17/18	3/16" MAX (4.75 mm)	•	•	•	•			•	•								•	•	•			•									•					•
—	AdvantaSand	3/16" MAX (4.75 mm)							•																												
21A	11	1" MAX (25.0 mm)					•			•	•									•	•					•	•					•				•	
21B	12	1 3/16" MAX (37.5 mm)						•		•	•									•	•					•	•					•				•	
25-26	25-26	3/4" MAX (19.0 mm)						•		•	•									•	•					•	•					•				•	
Gabion*	39	GABION*											•	•						•										•					•	•	
Rip Rap*	40-43	RIP RAP*										•																							•	•	